



4" BORE X 16" STROKE
 1" NITRIDE ROD WITH 3/4"-16 MALE ROD THD
 BDC-07M ROD CLEVIS W/ 3/4" PIN
 3/8" NPT PORTS POS 2
 MOUNT = CAP FIXED CLEVIS W/ 3/4" PIN
 STANDARD USE

PIN TO PIN = 26"
 PIN TO SHOULDER = 23.875"

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN INCHES
 REMOVE BURRS, BREAK SHARP EDGES R.010
 ANGULAR: MACH ± .5 DEGREES
 ONE PLACE DECIMAL ± .02
 TWO PLACE DECIMAL ± .01
 THREE PLACE DECIMAL ± .005
 MACHINED SURFACE FINISH

THIRD ANGLE PROJECTION

MATERIAL	
FINISH	
DO NOT SCALE DRAWING	

HIGGINSON

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HIGGINSON EQUIPMENT INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HIGGINSON EQUIPMENT INC. IS STRICTLY PROHIBITED

PART NUMBER: EA4S160D2N092NS	
DESCRIPTION: EA4S160D2N092NS	
SIZE B	DWG. NO.
REV 0	
SCALE: 1:5	WEIGHT: 20.24
SHEET 1 OF 1	